

EPSON SureColor P10000 44in Printer



Rating: 3.0

Price:

Variant price modifier:

Price with discount:

Salesprice with discount:

USD 3,247.00

Discount:



[Ask a question about this product](#)

Manufacturer: [Epson](#)

Description

Item: SCP10000SE

UPC: 010343928763

SPECIFICATIONS:

Printing: Advanced PrecisionCore microTFP 10-channel, drop-on-demand printhead with ink-repelling coating technology
Droplet: Smallest droplet size of 3.5 picoliters; Variable Droplet Technology can produce up to three different sizes per line

Ink Type	UltraChrome PRO pigment ink; 10-ink, 9-color Ink Configuration: C, LC, VM, VLM, Y, LGY, GY, DGY, PK, MK Nozzle: Color and monochrome, 800 nozzles x 10 color channels
Fade	Color: Up to 200 years Black-and-White: Up to 400 years

2400 x 1200 dpi

Print Speed	16 x 20" (40.6 x 50.8 cm) prints from 1:47 to 3:17; normal is 2:09 20 x 30" (50.8 x 76.2 cm) prints from 2:55 to 5:33; normal is 3:40 Epson ESC/P raster photographic drivers standard; optional internal Adobe PostScript 3 print server
--------------------	---

	In-box Cartridge Fill Volume: 110 mL each color x 10 colors total Retail Cartridge Fill Volume 700 mL each color x 10 colors total
--	---

Ink Shelf Life	2 years from printed production date or 6 months after opened
-----------------------	--

Roll	Single Top-Loading: 44" (111.8 cm) 2 or 3" (5.1 to 7.6 cm); user-adjustable roll media adapters
-------------	---

	6.7" (17 cm)
--	--------------

Cutter	High-speed internal rotary cutter; auto or manual cut
---------------	--

	Minimum Page Length: 11.24" (28.5 cm)
--	--

	Top/Bottom Margins Normal: Setting varies based on media selection Optional fixed: 3/3, 15/15, 35/15, 45/15
--	---

	Left/Right Margins: 0.1" (3 mm) each side; 0.24" (0.6 cm) total; or 0" at BorderFree sizes
--	--

Width	BorderFree Print: 10" (25.4 cm), 11.8" (29.9 cm), 13" (33 cm) (super A3), 16" (40.6 cm), 17" (43.2 cm) (US C), 20" (50.8 cm), 20.28" (51.5 cm) (~B2), 23.39" (59.4 cm) (~A1), 24" (60.9 cm), 28.86 (73.3 cm) (B1), 29" (73.7 cm), 33.11" (84.1 cm) (~A0), 36" (91.4 cm), 40.55" (103 cm) (~B0), 44" (111.8 cm) (Super B0)
--------------	--

	Paper Width: Minimum Paper Width: 10" (25.4 cm) Maximum Paper Width: 44" (111.8
--	--

cm)

Paper Roll Paper Remaining: Printable bar code tracking system
Top-loading if less than 19.7 mil (0.5 mm) thick

Media 31.5 to 59.1 mil (0.8 to 1.5 mm)

Top/Bottom: 0.12/0.59" (3/15 mm)
Top/Bottom Margins with Centering On: 0.6" (15 mm)
Left/Right Margins: 0.24" (6 mm) total

Sheet Size Minimum Cut-sheet Size: 8.5 x 11" (21.6 x 27.9 cm)
Minimum Recommended Cut Sheet: 13 x 19" (33 x 48.3 cm)
Maximum Printable Cut-sheet Length: 80" (203.2 cm)
Maximum Printable Roll Length: 590.55" (15 m)

Line A ±0.2% of specified length (±10.2 mil / 0.26 mm minimum)

Hi-Speed USB 2.0
1000Base-T Ethernet

Apple OS X 10.7 - 10.11.x
Microsoft Windows 10, 8.1, 7 (32-/64-bit)

Sound Pressure Level: Less than 50.5 dBA
Sound Power Level: Approximately 67.0 dBA

Operating: 50 to 95°F (10 to 35°C)
Operating (Recommended): 65 to 75°F (18 to 24°C)
Storage: -4 to 104°F (-20 to 40°C)

Operating: 20 to 80% (no condensation)
Operating (Recommended): 45 to 60% (no condensation)
Storage: 5 to 85% (no condensation)

Voltage: 110 to 240 VAC
Frequency: 50 to 60 Hz
Current: 5 A

Power Printing: Approximately 95 W
Sleep Mode: Approximately 2.8 W (1000BaseT Ethernet in Standby Mode)
Power Off: Less than 0.5 W (ENERGY STAR qualified)
Basket Open: 74 x 38.6 x 45.1" (187.9 x 97.6 x 114.5 cm)

278 lb (126 kg)



Limited 1-Year Warranty